

DIN RAIL FUSE HOLDERS

ASK Fuse Holder Series



ASK-4-3I
shown larger
than actual size.

- DIN Rail Mounted Fuse Holders
- 1-, 2-, and 3-Pole
- Models With Blown Fuse Indication
- 600V, 32 A (ASK 4)
- 600V, 50 A (ASK 6)

The ASK Series of DIN rail mounted fuse holders provides circuit protection for any industrial control system. Two standard fuse styles are supported: 14 x 51 mm (ASK 6) and 10 x 38 mm (ASK 4). Single pole, double pole, and 3 pole models are available, with or without blown fuse indicator lights. Fuses can be purchased separately (see accessories chart next page).

TECHNICAL DATA—FUSE HOLDERS

Maximum Operating Current:

ASK 4: 32A @ 600V

ASK 6: 50A @ 600V

Wire Range: 26–6 AWG

Dimensions:

ASK 4 (1 pole): 17.5 W x 81 mm H (0.69 x 3.2")

ASK 6 (1 pole): 27 W x 94 mm H (1.06 x 3.7")

Standards: IEC 60947-1, IEC 60947-3



ASK-6-1
shown larger
than actual size.

To Order	
MODEL NO.	DESCRIPTION
ASK-4-1	DIN rail fuse holder, 10 x 38 mm (0.39 x 1.50") fuses, 1-pole, no indicator light
ASK-4-2	DIN rail fuse holder, 10 x 38 mm (0.39 x 1.50") fuses, 2-pole, no indicator light
ASK-4-3	DIN rail fuse holder, 10 x 38 mm (0.39 x 1.50") fuses, 3-pole, no indicator light
ASK-4-1I	DIN rail fuse holder, 10 x 38 mm (0.39 x 1.50") fuses, 1-pole, with indicator light
ASK-4-2I	DIN rail fuse holder, 10 x 38 mm (0.39 x 1.50") fuses, 2-pole, with indicator light
ASK-4-3I	DIN rail fuse holder, 10 x 38 mm (0.39 x 1.50") fuses, 3-pole, with indicator light
ASK-6-1	DIN rail fuse holder, 14 x 51 mm (0.55 x 2.01") fuses, 1-pole, no indicator light
ASK-6-2	DIN rail fuse holder, 14 x 51 mm (0.55 x 2.01") fuses, 2-pole, no indicator light
ASK-6-3	DIN rail fuse holder, 14 x 51 mm (0.55 x 2.01") fuses, 3-pole, no indicator light
ASK-6-1I	DIN rail fuse holder, 14 x 51 mm (0.55 x 2.01") fuses, 1-pole, with indicator light
ASK-6-2I	DIN rail fuse holder, 14 x 51 mm (0.55 x 2.01") fuses, 2-pole, with indicator light
ASK-6-3I	DIN rail fuse holder, 14 x 51 mm (0.55 x 2.01") fuses, 3-pole, with indicator light

Ordering Examples: ASK-4-1, DIN rail mount fuse holder for 10 x 38 mm (0.39 x 1.50") fuses, 1-pole.

ASK-6-3I, DIN rail mount fuse holder for 14 x 51 mm (0.55 x 2.01") fuses, 3-pole, with indicator light.

ACCESSORIES

MODEL NO.	DESCRIPTION
DUAL ELEMENT 250V TIME DELAY FUSES FOR ASK6 SERIES	
ECNR1	Fuses, 250V, 1 A
ECNR2	Fuses, 250V, 2 A
ECNR3	Fuses, 250V, 3 A
ECNR5	Fuses, 250V, 5 A
ECNR10	Fuses, 250V, 10 A
ECNR15	Fuses, 250V, 15 A
ECNR20	Fuses, 250V, 20 A
ECNR25	Fuses, 250V, 25 A
ECNR30	Fuses, 250V, 30 A
GENERAL PURPOSE 250V CLASS M TIME DELAY FUSES FOR ASK4 SERIES	
MEN1	Fuses, 250V, 1 A
MEN2	Fuses, 250V, 2 A
MEN3	Fuses, 250V, 3 A
MEN5	Fuses, 250V, 5 A
MEN10	Fuses, 250V, 10 A
MEN15	Fuses, 250V, 15 A
MEN20	Fuses, 250V, 20 A
MEN25	Fuses, 250V, 25 A
MEN30	Fuses, 250V, 30 A
GENERAL PURPOSE 500V CLASS M TIME DELAY FUSES FOR ASK4 SERIES	
MEQ1	Fuses, 500V, 1 A
MEQ2	Fuses, 500V, 2 A
MEQ3	Fuses, 500V, 3 A
MEQ5	Fuses, 500V, 5 A
MEQ10	Fuses, 500V, 10 A
MEQ15	Fuses, 500V, 15 A
MEQ20	Fuses, 500V, 20 A
MEQ25	Fuses, 500V, 25 A
MEQ30	Fuses, 500V, 30 A
FAST ACTING 600V CLASS CC FUSES FOR ASK4 SERIES	
HCLR.5	Fuses, 600V, 0.5 A
HCLR.75	Fuses, 600V, 0.75 A
HCLR1	Fuses, 600V, 1 A
HCLR1.5	Fuses, 600V, 1.5 A
HCLR2	Fuses, 600V, 2 A
HCLR2.5	Fuses, 600V, 2.5 A
HCLR3	Fuses, 600V, 3 A
HCLR3.5	Fuses, 600V, 3.5 A
HCLR4	Fuses, 600V, 4 A
HCLR5	Fuses, 600V, 5 A
HCLR6	Fuses, 600V, 6 A
HCLR7	Fuses, 600V, 7 A
HCLR8	Fuses, 600V, 8 A
HCLR9	Fuses, 600V, 9 A
HCLR10	Fuses, 600V, 10 A
HCLR12	Fuses, 600V, 12 A
HCLR15	Fuses, 600V, 15 A
HCLR20	Fuses, 600V, 20 A
HCLR25	Fuses, 600V, 25 A
HCLR30	Fuses, 600V, 30 A

Note: For our entire selection of fuses visit us online.

ASK-6-11
shown larger
than actual size.



ASK-4-1
shown larger
than actual size.



MODEL NO.	DESCRIPTION
FAST ACTING 250V MIDGET CLASS FUSES FOR ASK4 SERIES	
MOL.5	Fuses, 250V, 0.5 A
MOL1	Fuses, 250V, 1 A
MOL1.5	Fuses, 250V, 1.5 A
MOL2	Fuses, 250V, 2 A
MOL2.5	Fuses, 250V, 2.5 A
MOL3	Fuses, 250V, 3 A
MOL4	Fuses, 250V, 4 A
MOL5	Fuses, 250V, 5 A
MOL6	Fuses, 250V, 6 A
MOL8	Fuses, 250V, 8 A
MOL10	Fuses, 250V, 10 A
MOL15	Fuses, 250V, 15 A
MOL20	Fuses, 250V, 20 A
MOL25	Fuses, 250V, 25 A
MOL30	Fuses, 250V, 30 A
FAST ACTING 600V MIDGET CLASS FUSES FOR ASK4 SERIES	
MCL.5	Fuses, 600V, 0.5 A
MCL1	Fuses, 600V, 1 A
MCL1.5	Fuses, 600V, 1.5 A
MCL2	Fuses, 600V, 2 A
MCL2.5	Fuses, 600V, 2.5 A
MCL3	Fuses, 600V, 3 A
MCL3.5	Fuses, 600V, 3.5 A
MCL4	Fuses, 600V, 4 A
MCL5	Fuses, 600V, 5 A
MCL6	Fuses, 600V, 6 A
MCL8	Fuses, 600V, 8 A
MCL10	Fuses, 600V, 10 A
MCL12	Fuses, 600V, 12 A
MCL15	Fuses, 600V, 15 A
MCL20	Fuses, 600V, 20 A
MCL25	Fuses, 600V, 25 A
MCL30	Fuses, 600V, 30 A
DIN RAIL	
XBANS3575P	DIN rail, 35 x 7.5 mm x 2 m (1.4 x 0.30" x 6.6'), slotted
XBANS3575U	DIN rail, 35 x 7.5 mm x 2 m (1.4 x 0.30" x 6.6'), solid
XBANS3515P	DIN rail, 35 x 15 mm x 2 m (1.4 x 0.60" x 6.6'), slotted
XBANS3515U	DIN rail, 35 x 15 mm x 2 m (1.4 x 0.60" x 6.6'), solid
XBANS3575PL	DIN rail, 35 x 7.5 mm x 2 m (1.4 x 0.30" x 6.6'), slotted, aluminum