

¼ DIN Digital Temperature and Limit Controllers

TRODEKS®

CN8100 Series



CN8121

- ✓ Large, Easy-to-Read LED, Selectable for Either Setpoint or Process Temperature
- ✓ Type J or K Thermocouple Input
- ✓ Adjustable Output Hysteresis to Prevent Rapid Cycling Around Setpoint Temperature
- ✓ Adjustable Deviation Alarm Flashes When Measured Temperature Exceeds or Falls Below Setpoint Temperature
- ✓ NEMA 4X (IP65) Front Bezel, Splash-Proof and Resistant to Dust
- ✓ Discrete Status Indicators Illuminate When Temperature Display, Setpoint Display or Heat/Cool Output Is Active
- ✓ Auto Tuning (CN8101 and CN8102)

The CN8100 Series controller is a low-cost, general purpose ¼ DIN temperature controller, ideal for OEM or replacement applications. Microprocessor-based and accurate to ±0.3% FS, it may be ordered as either a PID controller, on/off controller or limit safety device.

As a separate safety feature to your control application, the CN8121-R1 limit controller provides reliable high/low temperature limit shut-off control for most machine and process control applications including environmental chambers, furnaces,

ovens and packaging machinery. As a high-limit device, these controllers have a normally energized SPST latching output relay which becomes de-energized whenever the process variable (PV) exceeds a selected setpoint value. Reset of the latching output relay is done by holding the parameter button for 3 seconds on the front panel of the controller, or by cycling power to the controller.

Specifications

General

Line Voltage: 85 to 250 Vac, 50/60 Hz, 120 to 300 Vdc (auto polarity)

Display: 3-digit, 14 mm (0.56") orange LED

Discrete Indicators:

Setpoint: Amber

Actual: Amber

Heat: Orange

Cool: Orange



Panel punches available

CN8102-R1-R2, dual output PID controller shown smaller than actual size.

Power Consumption:

Less than 6 VA (instrument)

Front Panel Rating: NEMA 4X (IP65)

Operating Temperature:

0 to 60°C (32 to 140°F)

Humidity Tolerance: 90% RH maximum, non-condensing

Memory Protection:

Solid-state, non-volatile memory

Connections: Fast-on style (0.250" wide)

Panel Cutout: ¼ DIN, 92 mm² (3.622 in²)

Dimensions: 96 x 96 x 6.35 mm bezel (3.78 x 3.78 x 0.25")

Panel Depth: 88.9 mm (3.5")

Weight: 737 g (1 lb. 10 oz)

Performance

Accuracy: ±0.3% of FS, ±1 digit

Setpoint Resolution: 1 count

Repeatability: ±1.0 count

Temperature Stability: 5µV/°C maximum

TC Cold End Tracking:

±0.05°C/ °C ambient

Noise Rejection: Common mode

>100 dB, Series mode >70 dB

Process Sampling: 3.7 Hz (270 ms)**Available Inputs:****Thermocouple:****CN8110:** Type J**CN8120:** Type J**CN8100:** Type J or KMaximum lead resistance,
100 Ω for rated accuracy**Control Characteristics:****Control Hysteresis:** 1 to 140°C
(2 to 252°F)**Display Offset:** -70 to 70°C
(-126 to 126°F)**Deviation Alarm:** Off, 1 to 140°C
(Off, 1 to 252°F)**Outputs:** Electromechanical relay,
5 A @ 250 Vac, 5 A @ 30 Vdc,
solid-state relay, 120/240 Vac,
0 voltage switched, 2 A continuous
(output 1), 0.5 A continuous (output 2)
10 A surge @ 25°C (77°F), pulsed DC
5V for external SSR

CN8121-R1.

CN8111-R1.

CN8102-R1-R2.

Controllers shown
smaller than actual size.**Output Options**

Output Type	First Output Suffix- Heat Only (Reverse)	Second Output Suffix- Alarm (CN8112) or Cool Only (Direct—CN8102)
5 A Relay	-R1	-R2
AC SSR	-T1	-T2
DC Pulse	-D1	-D2

*Note: “-T1” = 2A ac SSR, “-T2” = 1A ac SSR.***Input Types, Ranges and Setpoint Limits, °C/°F Switchable**

Input Types for PID Control	Range
J Iron–Constantan	0 to 485°C (32 to 905°F)
K CHRTRODEKS®–ALTRODEKS®	-17 to 537°C (0 to 999°F)
Input Type for On/Off and Limit	Range
J Iron–Constantan	0 to 485°C (32 to 905°F)

To Order	
Model No.	Description
CN8101-(*)	PID controller, single output with Type J and K thermocouple input
CN8102-(*)-(*)	PID controller, dual output with Type J and K thermocouple input
CN8111-(*)	On/off controller, single output with Type J thermocouple input
CN8112-(*)-(*)	On/off controller, single control output and alarm output with Type J thermocouple input
CN8121-R1	High-limit controller, single relay output with Type J thermocouple input, FM approved
DPP-6	¼ DIN panel punch

Comes complete with operator's manual.