


DIN Rail Mount AC Voltage/Current Signal Conditioners



**DRA-ACT-SI Series AC
Current Input**
**DRA-ACT-SV Series AC
Voltage Input**



- ✓ Self-Powered
- ✓ ±0.1% Accuracy
- ✓ Isolated
- ✓ Low Profile Enclosure

The DRA-ACT-SI and DRA-ACT-SV Series are self-powered ac current and ac voltage input DIN rail mount signal conditioners that use the measured input to produce an accurate and linear output current. These signal conditioners have excellent accuracy, linearity and stability which make them unique.

The DRA-ACT-SI Series of ac current input models includes models for 0 to 1 Aac and 0 to 5 Aac inputs with a choice of either 0 to 1 mA or 0 to 20 mA output. The DRA-ACT-SV Series of ac voltage input models includes models for 0 to 150 Vac and 0 to 300 Vac inputs again with a choice of either 0 to 1 mA or 0 to 20 mA output. The output current from all of these self-powered models always starts at 0 mA since these units are powered from the measured signal. Therefore, when the ac current or voltage input is zero, the output is zero.

For complete safety, an internal transformer isolates the signal conditioner input from the output thus enabling these units to withstand large momentary inputs. The input to output isolation provides high output signal-to-noise ratio which makes these signal conditioners highly immune to ground loop signals and RFI.

Specifications

GENERAL

Accuracy: ±0.1% (for 5 to 120% of span) typical; ±0.15% max

Linearity: < ±0.1% (for 5 to 120% of span) typical; ±0.15% max

Temperature Stability: < 0.01%/°C

Power Supply: Self-powered from measured input



Isolation: 4 KV RMS/1 minute
Output: 0 to 1 mA, 0 to 20 mA
Output Ripple: < ± 0.1% of span
Response Time: < 240 msec (10 to 90%)

Frequency: 40 to 400 Hz

Frequency Variation Effect: < ± 0.02%/Hz

Max Output Loop Impedance:
 $R_{max} (\Omega) = 16/0.02 = 800 \Omega$ max @ 20 mA

Operating Ambient: -20 to 70°C (-4 to 158°F); 5 to 95% Rh, noncondensing

Storage Temperature: -40 to 90°C (-40 to 194°F)

Enclosure: Polycarbonate

Mounting: Standard 35 mm DIN rail or wall mount

Dimensions: 73 x 32.5 x 114 mm (2.87 x 1.28 x 4.49")

Weight: 0.7 lb (0.3 kg)

DRA-ACT-SI SERIES (AC CURRENT INPUT)

Input: 0 to 1 Aac, 0 to 5 Aac

Overrange: 6 Aac (for full accuracy)

Overload: 10 Aac continuous

Peak Overload: 40 Aac for 5 seconds every 10 minutes

Input Power Consumption: 0.6 VA @ 5 A input

Load Variation Effect: < ±0.02% for full load change

DRA-ACT-SV (AC VOLTAGE INPUT)

Input: 0 to 150 Vac, 0 to 300 Vac

Overrange: +20% of span (for full accuracy)

Overload: +40% of span continuous

Input Power Consumption: 0.9 VA @ 300 Vac input

To Order

Model No.	Description
DRA-ACT-SI-1	ac current, 0 to 1 Aac input, 0 to 1 mA output
DRA-ACT-SI-2	ac current, 0 to 5 Aac input, 0 to 1 mA output
DRA-ACT-SI-3	ac current, 0 to 1 Aac input, 0 to 20 mA output
DRA-ACT-SI-4	ac current, 0 to 5 Aac input, 0 to 20 mA output
DRA-ACT-SV-1	ac voltage, 0 to 150 Vac input, 0 to 1 mA output
DRA-ACT-SV-2	ac voltage, 0 to 300 Vac input, 0 to 1 mA output
DRA-ACT-SV-3	ac voltage, 0 to 150 Vac input, 0 to 20 mA output
DRA-ACT-SV-4	ac voltage, 0 to 300 Vac input, 0 to 20 mA output