## Rugged, Weatherproof, Wall Mounted **Temperature Sensor** Pt100 Class A Sensor in NEMA 4X (IP65) Enclosure



- Designed for Indoor and Outdoor Use
- Screw Terminal Block for 4-Wire Pt100 Connection
- Optional Built in 4 to 20 mA Transmitter
- Rugged Sensor and **Protection Tube Design**
- ✓ Supplied with NEMA 4X (IP68) Cable Gland or Electrical Connection

TRODEKS's new air temperature sensors offer the perfect solution for temperature monitoring outdoors or in demanding environments.

A rugged 6 mm-diameter sheathed RTD probe is housed in the center of a 14 mm (0.551") outer protection tube which is drilled to improve airflow around the sensor. A 4-terminal connector block or 4 to 20 mA transmitter are housed in a tough aluminum alloy enclosure rated to NEMA 4X (IP65).

A cable gland is fitted on the left hand side of the enclosure, suitable for cables from 2.5 to 6.5 mm (0.098 to 0.25") diameter.

EWSE-PT100 with customer supplied connection installed shown actual size.

## Specifications

## Dimensions:

75 mm Box: 80 W x 75 H x 58 mm D (2.95") (3 x 2.9 x 2.3") Sensor: 75 mm long x 14 mm OD (2.9 x 0.55")

TRODEKS

Maga Crive.

100

EWSE SERIES

AIR TEMPERATURE SENSOR

Omega Engineering Inc.

ntord CT 06507-0047 Tel: 800 825-6342

Cable Entry: NEMA 4X (IP68) gland for 2.5 to 6.5 mm (0.098 x 0.25") OD cable

EWSE-PT100:

Sensor Type: Thin film Pt100 class A 4 wire

**Ambient Temperature Range:** -50 to 100°C (-58 to 212°F)

**Electrical Connection:** Screw terminal block

EWSE-PT100-TX: Ambient Temperature Range: -40 to 85°C (-40 to 185°F) at 10 to 90% RH non condensing

Standard Transmitter Scaling: 4 mA -25°C (-13°F), 20 mA at 75°C Electrical Connection: Screw terminals, 2-wire Power Supply: 10 to 30 Vdc, loop powered Maximum Output Load: [(V supply-10)/20] kΩ eg 700Ω @ 24V

**To Order** Model No. Description EWSE-PT100 External air temperature assembly, 4-wire RTD EWSE-PT100-TX External air temperature assembly with 2-wire 4 to 20 mA transmitter **TX-SCALED** Factory scaling charge for non-standard temperature range on 4 to 20mA output models **TX4-100** Multi-conductor hook-up wire, 30.5 m (100') spool

Other probe lengths available on request. Contact sales to discuss your specific requirements. Ordering Example: EWSE-PT100, air temperature sensor.

