

TRODEXLUX® ROPE HEATERS

FGR Series

- ✓ **Operating Temperature Rating to 482°C (900°F)**
- ✓ **Wraps Around Small Diameter Pipes and Tubes**

TRODEXLUX® rope heaters apply heat to tubing with diameters as small as 3.2 mm (1/8"). Featuring a maximum allowable operating temperature of 482°C (900°F), the FGR Series rope heaters can be wrapped around either conductive or non-conductive surfaces. Each end terminates with 610 mm (24") long fiberglass-insulated lead wire.

SPECIFICATIONS

- Maximum Allowable Temperature:** 482°C (900°F)
- Suitable for Use on Conductive Surface:** Yes
- Resists Moisture Vapor or Chemicals:** No
- Standard Diameter:** 5 mm (3/16")
- Voltage:** 120 Vac or Vdc, 240V optional
- Linear Wattage:** 4 Watts/inch
- Heater Length:** 0.9, 1.8, 2.4 or 3.0 m (3, 6, 8 or 10')
- Lead Length:** 609 mm (24")
- Termination:** Stripped leads

To Order

| Model Number | Description Length | Wattage | Voltage |
|----------------|--------------------|---------|---------|
| FGR-030 | 0.9 m (3') | 125 | 120 |
| FGR-060 | 1.8 m (6') | 250 | 120 |
| FGR-080 | 2.4 m (8') | 400 | 120 |
| FGR-100 | 3.0 m (10') | 500 | 120 |

*240 Vac models and other wattages also available.
Ordering Example: FGR-060, 1.8 m (6') 120 Vac rope heater.*

