

Economical Handheld Thermometer With Magnet Hanger

POCKET PAL™

HH74K



Standard
No Points

- ✓ Lightweight Design
- ✓ Pocket Hook and Magnet Hanger
- ✓ ADJ Thermocouple Offset Function
- ✓ Max/Data Hold Function
- ✓ Auto Power-Off Function Can be Disabled
- ✓ Battery Life 300 Hours Typical Use
- ✓ °C or °F Switchable
- ✓ NIST-Traceable Certificate of Calibration (No Points)

Specifications

Display: 3½ digit LCD

Low-Battery Indication:

The "batt" is displayed

Measurement Rate: 2.5 times per second

Operating Environment: 0 to 50°C (32 to 122°F) @ <70% RH

Storage Environment: -20 to 60°C (-4 to 140°F), 0 to 80% RH with battery removed from meter

Stated Accuracy: 23 ±5°C (73 ± 9°F), <75% RH

Battery: Three 1.5V "AAA" (included)

Battery Life: 300 hours, typical use

Temperature:

Range: -100 to 850°C (-148 to 1562°F)

Resolution: 1°C or 1°F, 0.1°C or 0.1°F

Accuracy (Does Not Include Probe):

18 to 28°C (64 to 82°F) ambient

±(0.3% rdg + 1°C) on °C ranges

±(0.3% rdg + 2°F) on °F ranges

Resolution	Range
0.1°C	-59.9 to 199.9°C
1°C	-100 to -60°C 200 to 850°C
0.1°F	-59.9 to 199.9°F
1°F	-148 to -60°F 200 to 1562°F

Dimensions: 148 H x 48 W x 24 mm D (5.8 x 1.9 x 0.94")

Weight: Approximately 74 g (2.6 oz) with battery

Connector: SMP

Applications

- ✓ Greenhouses
- ✓ Office Environment
- ✓ Environmental Studies
- ✓ Labs
- ✓ Workshops
- ✓ Art Galleries/Museums
- ✓ Weather Monitoring
- ✓ Department Stores



HH74K shown with optional SA1-K-SC, self-adhesive thermocouple.



Free Thermocouple Included!

HH74K models include a free 1 m (40") Type K insulated beaded wire thermocouple with subminiature connector and wire spool caddy (1 per channel). **Order a Spare!**

Model No. SC-GG-K-30-36



HH74K shown actual size.

To Order

Model No.	Description
HH74K	Type K thermometer
SC74	Soft carrying case

Comes complete with operator's manual, thermocouple, magnet hanger, NIST certificate (no points) and 3 "AAA" batteries.

Ordering Example: HH74K, Type K thermometer with magnet hanger.