

# ECONOMICAL DIGITAL HANDHELD MANOMETER 0 to 20 inH<sub>2</sub>O RANGE

## HHP680



- ✓ Max and Reading Hold
- ✓ Portable and Easy-to-Use
- ✓ Auto-Zero Power
- ✓ Switchable High Resolution:  
0.01/0.1" Water Column
- ✓ Comes with Tubing [60 cm (24")]  
and 1/8" NPT Fitting
- ✓ 4 "AAA" Alkaline  
Batteries Included
- ✓ Soft Carrying Case

The HHP680 is a low-cost, versatile handheld manometer. It comes with tubing, fitting, soft carrying case, and batteries. Typical applications include commercial and automotive HVAC.

### SPECIFICATIONS

**Display:** 3½ digit LCD with a maximum reading of 1999

**Range:** 0 to 20 inH<sub>2</sub>O

**Resolution:** 0.01/0.1"

**Low-Battery Indicator:**  
The "⊕" displays

**Storage Temperature:**  
-20 to 60°C (-4 to 140°F)

**Operating Temperature:**  
0 to 40°C (32 to 104°F)

**Operating Relative Humidity:**  
15 to 90% RH, non-condensing

**Accuracy:** ±2% at 23°C (73°F)  
[±5°C (9°F), <75% RH]

**Dimensions:** 190 H x 44 W x 40 mm D  
(7.5 x 1.7 x 1.6")

**Weight:** Approx. 150 g (5.3 oz)  
with batteries

**Batteries:** 4 "AAA" (included)

**Sensor:** Solid state

**Battery Life:** 150 hrs, typical usage; no measurable current when in off position

**Compatible Media:** Dry,  
non-corrosive gases



**VERSATILE!**

60 cm (24") of  
tubing and 1/8" NPT  
adaptor included.

HHP680, shown  
actual size.

A

PRESSURE INSTRUMENTS

### To Order

MODEL NO.	DESCRIPTION
HHP680	Portable manometer with 0 to 20 inH <sub>2</sub> O range

*Comes complete with 60 cm (24") of tubing, fitting, 4 "AAA" alkaline batteries, soft carrying case and operator's manual.*

**Ordering Example:** HHP680, handheld manometer.