


Four Port Automatic ISA RS422/485 Interface



OMG-ULTRA-COMM422, shown smaller than actual size.

OMG-ULTRA-COMM422



- ✓ Automatic Control of RS485 Driver Enable
- ✓ Selectable Address Including COM1: - COM4: and Other I/O Addresses or 32 Consecutive I/O Locations
- ✓ Selectable and Sharable IRQ Level (2-5, 7, 10-12, and 15)
- ✓ On Board Interrupt Status Port for Greater Throughput
- ✓ Compatible with Existing Communication Drivers
- ✓ Data Rates Supported up to 460K bps
- ✓ Selectable Termination, Echo Mode, Two or Four Wire Operation
- ✓ DB-9P Connectors Providing TD, RD, RTS and CTS
- ✓ Includes Windows Advanced COM: Drivers and Help Files to Simplify Installation

The OMG-ULTRA-COMM422 provides the PC with four RS485/422 Asynchronous links to data collection or other devices. Windows XP/Vista/7 drivers are included. The drivers provide IRQ sharing, advanced UART support and serial diagnostic utilities.

Storage Temperature: -20 to 70°C (-4 to 158°F)
Humidity Range: 10 to 90% RH
Current Specifications: +5V @ 600 mA
Connector(s): Onboard DB-37S to (4) DB-9P
Dimensions: 18.54 L x 10.67 cm H (7.3 x 4.2")

Specifications
Communications Chip: 16550 UART
Number of Ports: Four RS422/485
Max. Data Rate: 460K bps
Max. Data Distance: Up to 1524 m (5000')
RS485 Operation: two or four wire
Operating Temperature: 0 to 50°C (0 to 122°F)

To Order	
Model No.	Description
OMG-ULTRA-COMM422	Four port automatic RS422/485 interface (spider cable included)