


# Unique Surface Probes

TRODEKS®

All the probes in this series meet the Standard Limits of Error.



**Model No. 88203(\*)**  
**Model No. 98203(\*)**  
**with Swivel Head**

For rotating, smooth metallic surfaces of 229 to 610 mm (9 to 24") in diameter. 90 m (300') per minute maximum surface velocity. Maximum surface temperature of 205°C (400°F).

Replaceable Element supplied free, for additional elements order **Model No. 88203(\*)-RE**.

**Model No. 88201(\*)**  
**Model No. 98201(\*)**  
**with Swivel Head**

A roller-surface probe, for use on moving or rotating, smooth surfaces with a velocity up to 61 m (200') per minute. Maximum surface temperature of 205°C (400°F).

Replaceable Element supplied free, for additional elements order **Model No. 88201(\*)-RE**.

Visit us online for dimensions.

**Model No. 88202(\*)**  
**Model No. 98202(\*)**  
**with Swivel Head**

A roller-surface probe, ideal for measuring outside wall temperatures of smooth plastic or steel piping. Can be used on moving or rotating surfaces of 559 to 1524 mm (22 to 60") in diameter, with 90 m (300') per minute maximum surface velocity. Maximum surface temperature of 205°C (400°F).

Replaceable Element supplied free, for additional elements order **Model No. 88202(\*)-RE**.

**Ordering Example: 98201K**, style 98201 swivel head roller surface probe in Type K thermocouple.

**\* Specify Calibration:**  
**K: CHROMEKA®-ALOMEGA®**  
**E: CHROMEKA®-Constantan**

