

Very High Temperature Laboratory Blackbody Calibration Source

BLACK POINT™
BB705



BB705.



- ✓ Calibrates From 100 to 1046°C (212 to 1915°F)
- ✓ Built-In Reference Temperature Display
- ✓ Large 44.5 mm (1.75") Aperture
- ✓ Calibrates Infrared Pyrometers Quickly and Accurately
- ✓ Built-In PID Autotune Control with Digital Readout
- ✓ NIST-Traceable Calibration Certificate Included with 3 Data Points
- ✓ RS232 Communication Standard**

Specifications

Ambient Temperature:

0 to 35°C (32 to 95°F)

Power: 115 Vac 50/60 Hz or 230 Vac 50/60 Hz

Operating Temperature

Range (Blackbody Cavity): 100 to 1046°C (212 to 1915°F)

Internal Sensing Elements:

Platinum thermocouples

Stability: 0.4°C (0.7°F) per 8-hour period

Accuracy:

±0.25% of reading; ±1°C

Cavity Emissivity: 0.99

Warm-up Time: 80 minutes from 100°C to 1000°C

Dimensions:

566 W x 520 H x 600 mm D (22.3 x 20.5 x 23.6")

Cavity Opening: 44.5 mm (1.75")

Weight: 31 kg (68 lb)



Caution: To avoid fire hazard or damage to your calibrator, always allow your calibrator to cool down to ambient temperature before returning to storage.



Shown calibrating OS523 Series high temperature infrared pyrometer. See omega.com for details.

To Order		<i>bb705 for Pricing and Details</i>	
Model No.		Description	
BB705		Blackbody, 110 Vac	
BB705-230VAC*		Blackbody, 230 Vac, CE	