



Non-Reversible TRODEXLABLE® Temperature Monitors

Micro-Dot Series


(Model number is °F temperature rating preceded by letters "MD"), MD-(*)

Outside Diameter: 5 mm (0.2")

Indicating Window: 1.3 mm (0.05")



Micro-dot labels shown actual size.



Bulls-eye labels shown actual size.

Bulls-Eye Series

(Model number is temperature rating preceded by letters "BE"), BE-(*)

Outside Diameter: 8 mm (0.315")

Indicating Window: 3 mm (0.13")

Micro-Dot Series and Bulls-Eye Series are available in single temperature ratings listed below:

°C	38	43	49	52	54	60	66	71	77	79	82	88	93
°F	100	110	120	125	130	140	150	160	170	175	180	190	200
°C	99	104	107	110	116	121	127	132	135	138	143	149	
°F	210	220	225	230	240	250	260	270	275	280	290	300	

To order package of 30, add suffix "-30" to model number.

Ordering Examples: BE-210F-30, bulls-eye label, 99°C (210°F), package of 30.

MD-100F-30, micro-dot label, 38°C (100°F), package of 30.

Specifications

Accuracy: Up to 99°C (210°F) is ±1°C (1.8°F); from 100°C (212°F) to 154°C (309°F) is ±1.5°C (2.7°F); from 160°C (320°F) to 280°C (536°F) is ±1% and ±1°C (1.8°F)

Four temperature ratings on each label

4A: 5 to 6°C (10°F) between each rating

4B: 14°C (25°F) between each rating

4C: 28°C (50°F) between each rating

Specifications

Accuracy: Up to 99°C (210°F) is ±1°C (1.8°F); from 100°C (212°F) to 154°C (309°F) is ±1.5°C (2.7°F); from 160°C (320°F) to 280°C (536°F) is ±1% and ±1°C (1.8°F)

4A, 4B, 4C Labels

(4 Temperatures per label)

Model No.	Temperature Ratings			
4A-100	°C 38	43	49	54
	°F 100	110	120	130
4A-110	°C 43	49	54	60
	°F 110	120	130	140
4A-120	°C 49	54	60	66
	°F 120	130	140	150
4A-130	°C 54	60	66	71
	°F 130	140	150	160
4A-140	°C 60	66	71	77
	°F 140	150	160	170
4A-150	°C 66	71	77	82
	°F 150	160	170	180

Model No.	Temperature Ratings			
4A-160	°C 71	77	82	88
	°F 160	170	180	190
4A-170	°C 77	82	88	93
	°F 170	180	190	200
4A-180	°C 82	88	93	99
	°F 180	190	200	210
4A-190	°C 88	93	99	104
	°F 190	200	210	220
4A-200	°C 93	99	104	110
	°F 200	210	220	230
4A-210	°C 99	104	110	116
	°F 210	220	230	240
4A-220	°C 104	110	116	121
	°F 220	230	240	250
4A-230	°C 110	116	121	127
	°F 230	240	250	260
4A-240	°C 116	121	127	132
	°F 240	250	260	270
4A-250	°C 121	127	132	138
	°F 250	260	270	280
4A-260	°C 127	132	138	143
	°F 260	270	280	290
4A-270	°C 132	138	143	149
	°F 270	280	290	300
4A-280	°C 138	143	149	154
	°F 280	290	300	310
4A-290	°C 143	149	154	160
	°F 290	300	310	320
4A-300	°C 149	154	160	166
	°F 300	310	320	330
4A-310	°C 154	160	166	171
	°F 310	320	330	340
4A-320	°C 160	166	171	177
	°F 320	330	340	350
4A-330	°C 166	171	177	182
	°F 330	340	350	360
4A-340	°C 171	177	182	188
	°F 340	350	360	370
4A-350	°C 177	182	188	193
	°F 350	360	370	380
4A-360	°C 182	188	193	199
	°F 360	370	380	390
4A-370	°C 188	193	199	204
	°F 370	380	390	400
4B-100	°C 38	52	66	79
	°F 100	125	150	175
4B-125	°C 52	66	79	93
	°F 125	150	175	200

Model No.	Temperature Ratings			
4B-150	°C 66	79	93	107
	°F 150	175	200	225
4B-175	°C 79	93	107	121
	°F 175	200	225	250
4B-200	°C 93	107	121	135
	°F 200	225	250	275
4B-225	°C 107	121	135	149
	°F 225	250	275	300
4B-250	°C 121	135	149	163
	°F 250	275	300	325
4B-275	°C 135	149	163	177
	°F 275	300	325	350
4B-300	°C 149	163	177	191
	°F 300	325	350	375
4B-325	°C 163	177	191	204
	°F 325	350	375	400
4B-350	°C 177	191	204	218
	°F 350	375	400	425
4B-375	°C 191	204	218	232
	°F 375	400	425	450
4B-400	°C 204	218	232	246
	°F 400	425	450	475
4B-425	°C 218	232	246	260
	°F 425	450	475	500
4C-100	°C 38	66	93	121
	°F 100	150	200	250
4C-150	°C 66	93	121	149
	°F 150	200	250	300
4C-200	°C 93	121	149	177
	°F 200	250	300	350
4C-250	°C 121	149	177	204
	°F 250	300	350	400
4C-300	°C 149	177	204	232
	°F 300	350	400	450
4C-350	°C 177	204	232	260
	°F 350	400	450	500
4C-400	°C 204	232	260	288
	°F 400	450	500	550

To order package of 30, add suffix "-30" to model number.

Ordering Examples: 4A-100-30, low range temperature label, 38, 43, 49, 54°C (100, 110, 120, 130°F), package of 30.

4C-200-30, low range temperature label, 93, 121, 149, 177°C (200, 250, 300, 350°F), package of 30.