

CHART-TEMP®

Temperature Recorders

CT-100 Series



Comes with
Extra Charts!



CT-300F-1H shown smaller than actual size.

From -40 to 260°C (-40 to 500°F)
Low-Temperature Recorders with Ranges Up to 104°C (220°F) and Either 1- or 7-Day Charts and 2% Accuracy
Oven Recorders with Ranges Up to 260°C (500°F) and Either 1- or 24-Hour Charts with 3% Accuracy

TRODEX® CHART-TEMP® recorders are dry-stylus, spring-wound, clock-driven circular chart recorders. Simply rewind the drive when replacing the chart. These recorders are excellent for recording temperatures inside buildings, refrigerators, or ovens. Units with ranges up to 260°C (500°F) are available.

Specifications

Dimensions: 82.5 H x 100 mm diameter (3.26 x 3.94")

Weight:

High-Temp Models: 397 g (14 oz)
Low-Temp Models: 600 g (21 oz)

Low-Temperature Recorders

To Order		
Model No.	Temperature Range	Charts Model No.
CT-100AF-(*)	0 to 100°F	(*)-100F
CT-120AF-(*)	20 to 120°F	(*)-120F
CT-160AF-(*)	-40 to 160°F	(*)-160F
CT-220AF-(*)	20 to 220°F	(*)-220F
CT-70AF-(*)	-30 to 70°F	(*)-70F

* Insert "1" for 1-day or "7" for 7-day recorder. Units with "-7" suffix are 7-day recorders. Comes with 100 charts each.

High-Temperature Recorders

Model No.	Temperature Range	Charts Model No.
CT-300F-(*)	70 to 300°F	(*)-300F-CHART
CT-400F-1H	70 to 400°F	(*)-400F-CHART
CT-500F-(*)	70 to 500°F	(*)-500F-CHART
CT-150C-1H	20 to 150°F	1H-150C-CHART
CT-200C-1H	20 to 200°C	1H-200C-CHART
CT-260C-1H	20 to 260°C	1H-260C-CHART

* Insert "1H" for 1-hour or "24H" for 24-hour recorder. Units with "-1H" suffix are 1-hour recorders.