

DC TO DC ISOLATED SIGNAL CONDITIONER FIELD RANGEABLE INPUTS AND OUTPUTS

TRODEKS®

Input: 0-10 mV to 0-130 Vdc, ± 5 Vdc,
 ± 10 Vdc, or 0-200 μ A to 0-50 mAdc
Output: 0-1V to 0-10 Vdc, ± 5 Vdc, ± 10 Vdc,
or 0-2 mA to 0-20 mAdc or 4-20 mA

DMD4380 Series

- ✓ Standard DIN Rail Mounting
- ✓ Fast Setup—Over 100 I/O Ranges
- ✓ Removable Connectors
- ✓ Full 3-Way Isolation
- ✓ Output Test Button
- ✓ Built-In Loop Powers for Sink/Source and I/O
- ✓ 80 to 265 Vac or 9 to 30 Vdc Input Power Options

Applications

- ✓ Amplify, Convert or Scale Process Signals
- ✓ Isolate Single Ended (Common Ground) PLC Inputs
- ✓ Interface Process Signals with Panel Meters, PLCs, Recorders, Data Acquisition, DCS and SCADA Systems

The DMD4380 accepts a dc voltage or current input and provides an optically isolated dc voltage or current output that is linear to the input. It provides filtering, amplifies, and converts the input signal to the selected dc voltage or current output that you select. The 3-way 1200V isolation eliminates ground loops, common mode voltages and greatly reduces noise pick-up. Standard features include a 15 Vdc loop power supply and a 20 Vdc loop supply for the output. The power supplies can also be wired to sink or source which allows



DMD4380, shown smaller than actual size with standard DIN rail (sold separately).

the DMD4380 to be used with any combination of powered or unpowered mA inputs and powered or unpowered mA outputs including passive mA devices. Features such as red and green LEDs that vary in intensity to show input and output activity and an output test button help make set-up and troubleshooting fast and easy.

SPECIFICATIONS

Input Ranges: Field selectable ranges via switch settings

Voltage: 0-10 mVdc to 0-50 Vdc

Bipolar Voltage: ± 50 mVdc to ± 10 Vdc

Current: 0-200 μ Adc to 0-50 mAdc

Input Impedance (Voltage):

Voltage: 1 M Ω minimum

Current: 50 Ω typical

Voltage Burden: 1 Vdc at 20 mA

Input Loop Power Supply:

15 Vdc $\pm 10\%$, regulated, 25 mAdc; max ripple, less than 10 mV RMS may be selectively wired for sinking or sourcing

Output Ranges:

Switch Selectable, Field Rangeable Voltage (10 mA max):

0-1 to 0-10 Vdc

Bipolar Voltage (10 mA max): ± 5 to ± 10 Vdc

Current: 0-2 mA to 0-25 mA

Compliance, Drive @ 20 mA: 20V, 1000 Ω drive

Output Offset: $\pm 100\%$ of span in 15% increments

Output Linearity: Better than $\pm 0.1\%$ of span

ACCESSORIES



Output Zero and Span: Multi-turn potentiometers to compensate for load and lead variations, $\pm 15\%$ of span adjustment range typical

Output Loop Power Supply: 20 Vdc nominal, regulated, 25 mA dc; max ripple, less than 10 mV RMS; may be selectively wired for sinking or sourcing

Output Ripple: <10 mV rms

Function Test Button: Sets output to test level when pressed; adjustable 0 to 100% of span via potentiometer. Factory default is approx. 50% of span

Response Time: 70 ms typical

Common Mode Rejection: 120 db minimum

Isolation: 1200 Vrms minimum, 3-way isolation, power to input, power to output and input to output

Operating Temperature Range: -10 to 60°C (14 to 140°F)

Thermal Stability: Better than $\pm 0.02\%$ of span per °C

Std. Power: 80 to 265 Vac, 50/60 Hz or 85 to 300 Vdc, 2 W maximum

Low Voltage Option: 9 to 30 Vdc or 10 to 32 Vac

Mounting: Mounts to standard 35 mm DIN rail

Environmental Protection: IP40

Connections: Four 4-terminal removable connectors 14 AWG max wire size

Dimensions: 22.5 W x 117 H x 122 mm D (0.89 x 4.62 x 4.81") height includes connectors

Weight: 150 g (5.3 oz)

ELECTRICAL CONNECTIONS

TYPE OF INPUT DEVICE	- TERMINAL	+ TERMINAL
Sensor of transmitter with a voltage output.	9(-)	11(+)
Transmitter with a mA (Current) output that provides power to the current loop. Typically a 3- or 4-wire device.	9(-)	11(+)
Transmitter with a mA (Current) output that is unpowered. Typically a 2-wire device. The DMD module provides the power.	11(-)	10(+15V)
TYPE OF OUTPUT DEVICE		
Measuring/recording device accepts a voltage input.	3(-)	4(+) switch E set to "V"
Measuring/recording device accepts a mA (current) input and the input is unpowered or passive. APD module provides the loop power.	3(-)	4(+20V) switch E set to "I"
Measuring/recording device accepts a mA (current) input and the input provides power to the loop power.	2(-)	3(+) switch E set to "I"

SETUP INPUT AND OUTPUT (See manual for full selection)

Input	0 to 1 mA	4 to 20 mA	0 to 50 mV	0 to 100 mV	0 to 500 mV	1 to 5V	0 to 5V	0 to 10V	$\pm 10V$	0 to 25V
Output	Rotary Switches	ABCDE	ABCDE	ABCDE	ABCDE	ABCDE	ABCDE	ABCDE	ABCDE	ABCDE
0 to 1V	4B00V	5590V	0B00V	0100V	0000V	1490V	2000V	2400V	1C30V	2800V
0 to 5V	4B09V	5599V	0B09V	0109V	0009V	1499V	2009V	2409V	1C39V	2809V
1 to 5V	4B06V	5596V	0B06V	0106V	0006V	1496V	2006V	2406V	1C36V	2806V
$\pm 5V$	4B04V	5594V	0B04V	0104V	0004V	1494V	2004V	2404V	1C34V	2804V
0 to 10V	4B03V	5593V	0B03V	0103V	0003V	1493V	2003V	2403V	1C33V	2803V
$\pm 10V$	4B05V	5595V	0B005V	0105V	0005V	1495V	2005V	2405V	1C35V	2805V
4 to 20 mA	4B07I	5597I	0B007I	0107I	0007I	1497I	2007I	2407I	1C37I	2807I

Example: 1 to 5V input, 4 to 20 mA output: **Code 1497I**. Set switch "A" to 1, "B" to 4, switch "C" to 9, switch "D" to 7 and switch "E" to I.

CONNECTIONS	
TERMINAL NO.	SIGNAL
3	Sig. Out -
4	Sig. Out +
9	Sig. Input -
10	Loop Exc.
11	Sig. Input +
13	Power +
16	Power -

To Order

MODEL NO.	DESCRIPTION
DMD4380	Standard voltage isolated DC to DC signal conditioner
DMD4380-DC	Low voltage isolated DC to DC signal conditioner

Comes complete with operator's manual.

Ordering Example: DMD4380, standard power, DC to DC isolated signal conditioner.