DRUM HEATERS

TRODEKS®

FCDH Series



- ✓ 55 Gallon Wraparound
- ✓ Easy-to-Use Digital Temperature Controller with Audible/ Visual Alarm
- ✓ Low Watt Density
- ✓ Silicone-Coated **Fiberglass Facing**
- ✓ 25 mm (1")
 Fiberglass Insulation
- ✓ Metal and Poly **Drum Models**

The FCDH Series consists of full-coverage insulated drum heaters that provide a safe and efficient method of temperature and viscosity control. An easy-touse digital temperature controller prevents temperature runaway. These heaters use a patented grounded heating element and are designed for indoor use when it is desirable to insulate the entire surface of the drum.

SPECIFICATIONS

Digital On/Off Temperature

Controllers:

Metal Drums: 10 to 232°C

(50 to 450°F)

Poly Drums: 10 to 71°C

(50 to 160°F)

Max Exposure Temperature:

260°C (500°F)

Outer Sheath: Silicone-coated

fiberglass facing

Inner Sheath: Silicone-coated

fiberglass liner

Insulation: 25.4 mm (1") fiberglass Dielectric Strength: Over 2000V Power Cord: 1.8 m (6') with plug on 120V models, stripped lead ends on

240V models

Power: 120 or 240 Vac



To Order				
Model No.	Description	Туре	Wattage	Voltage
FCDH-1600-120	Drum heater	Metal	1600	120
FCDH-750-120	Drum heater	Plastic	750	120
FCDH-1600-240	Drum heater	Metal	1600	240
FCDH-750-240	Drum heater	Plastic	750	240
Accessories				
FCDH-TOP	Drum top cover			
FCDH-STRIP	Expander strip for rolling drums with removable lids			

All drum heaters are for 55 gallon size and comes with a digital temperature controller. The 120 Vac models include a 3-prong plug, and the 240 Vac models have stripped leads. FCDH-TOP is an insulation cover that fits on the top of a drum to help prevent heat loss.