

4-Channel Handheld Data Logger Thermometer

TRODEKS®

HH374



No Points

- ✓ Auto Range
- ✓ USB Interface with Windows® Software
- ✓ LED Back Light
- ✓ HOLD Function
- ✓ 4-Channel Input, Type K Thermocouple
- ✓ 4-Channel Display Resolution
0.1°C/0.1°F with Windows® Software
- ✓ MAX/MIN/AVG Function
- ✓ Auto Shut-Off for Battery Saving
- ✓ 16,000 Records Data Logger Each Channel
- ✓ Certificate of Traceable Calibration Included (No Points)

The HH374 has a high resolution and fast analog to digital converter. Measurements settings and results are shown on the backlit LCD display. Data can be stored in the meter or directly saved on a computer through PC interface. Recorded data can be further processed on a computer. With the exclusive software, recording/recalling of data and programming of logging parameters can be done directly through a PC.

SPECIFICATIONS

Measurement Range: -200 to 1370°C (-328 to 2498°F)

Accuracy: -200 to 1370°C (-328 to 2498°F)
±0.1% rdg + 0.7°C (±0.1% rdg + 1.4°F)

Input Protection: 60 Vdc or 24 Vrms AC maximum

Battery Type: 9V battery (included)


Operating Condition: 0 to 50°C (32 to 122°F) (<80% RH)

Storage Condition: -20 to 60°C
(-4 to 140°F) (<70% RH)

System Required: Windows NT 4.0/NT2000/XP/Vista/Windows 7

Dimensions:
196 H x 65 W x 36 mm D
(7.72 x 2.56 x 1.42")

Approx Weight:
285 g (10.05 oz)



Free Thermocouples Included!

This model includes 4 free 1 m (40") Type K insulated beaded wire thermocouples with subminiature connector (1 per channel).

Order a Spare! Model No. SC-GG-K-30-36



HH374



HH374 comes complete with 4 beaded wire Type K thermocouples, 9V battery, hard carrying case, software, USB cable and operator's manual.

To Order

Model No.	Description
HH374	4-channel temperature data logger
HH300-ADAPTER	115 Vac adaptor

Comes complete with 4 beaded wire Type K thermocouples, 9V battery, hard carrying case, software, USB cable and operator's manual.