

TRODEXMETER® Mix and Match Series

Digital Multimeters with Non-Contact Voltage Audible Buzzer Feature



HHM33

Special Non-Contact Voltage Feature:
Meter Buzzer when Placed Near Live Electrical Circuits.



HHM34



HHM35

CHEAPER BY THE DOZEN!
Purchase any Combination of 12 Units and Save 20%

All models shown smaller than actual size.



Optional

3½ digit, 1999 Counts Digital Display
DC Volts: 0 to 2 V/20 V/600 V $\pm 1.2\%$
AC Volts: 0-200 V/600 V/50 to 500 Hz $\pm 2.5\%$
DC Current: 0 to 200 μ A/2 mA/20 mA/200 mA/10 A $\pm 2.5\%$
Resistance: 0 to 200 Ω /2 K Ω /20 K Ω /200 K Ω /20 M Ω $\pm 2.0\%$
Resolution: 1 mV, 100 mV, 0.1 μ A, 0.1 Ω
Battery Test: 1.5 V/9 V $\pm 3.5\%$
Diode Test
10A Fused
Safety Input Jacks
Safety Test Leads
Overload Protection on All Ranges

3½ digit, 1999 Counts Digital Display

DC Volts: 0 to 200 mV/2 V/20 V/600 V $\pm 1.2\%$
AC Volts: 0 to 200 mV/2 V/200 V/600 V/50 to 500 Hz $\pm 2.0\%$
DC Current: 0 to 200 μ A/20 mA/200 mA/10 A $\pm 1.5\%$
AC Current: 0 to 200 μ A/20 mA/200 mA/10 A/50-500 Hz $\pm 2.0\%$
Resistance: 0 to 200 Ω /2 K Ω /200 K Ω /20 M Ω $\pm 1.5\%$
Resolution: 100 μ V, 0.1 μ A, 0.1 Ω
Diode Test
Continuity Test
Non-Contact Voltage Indicator
 Low-tension lines from 70 to 440Vac 50 to 60 Hz
Data Hold, MAX Hold, 10A Fused, Safety Input Jacks, Safety Test Leads, Overload Protection on All Ranges

3200 Counts with Annunciators
Auto Power-Off Function
Auto or Manual Range Selection
Bar Graph Display: 12 time/sec sampling
DC Volts(Auto): 0 to 320 mV/3.2 V/32 V/320 V/600 V $\pm 1.2\%$
AC Volts(Auto): 0 to 3.2 V/32 V/320 V/600 V/50-200 Hz $\pm 2.0\%$
DC Current: 0 to 320 μ A/3200 μ A/32 mA/320 mA/10 A $\pm 2.0\%$
AC Current: 0 to 320 μ A/3200 μ A/32 mA/320 mA/10 A $\pm 2.5\%$
Resistance: 0 to 320 Ω /3.2 K Ω /320 K Ω /3.2 M Ω /30 M Ω $\pm 1.5\%$
Resolution: 100 μ V, 0.1 μ A, 0.1 Ω
Diode Test
Continuity Test, Data Hold, 10A Fused, Safety Input Jacks, Safety Test Leads, Overload Protection on All Ranges



Test leads included with all models shown.

To Order

Model No.	Description
HHM33	Basic DMM
HHM34	Voltage DMM with non-contact feature
HHM35	Multifunction DMM
HHM-TL	Spare set of test leads
HHM-NIST	NIST calibration certificate

Comes complete with test leads and operator's manual.

Ordering Example: HHM35, multifunction DMM and HHM-TL, spare set of test leads.