



U24Y101, shown smaller than actual size.

SPECIFICATIONS

Input:

- U24Y101: 110 Vac
- U24Y101-220: 220 Vac
- U48Y40: 110 Vac

Operating Range: -10 to 65°C
(14 to 150°F)

Output:

- U24Y101: 24 Vdc @ 1000 mA
- U48Y40: 48 Vdc @ 400 mA

Dimensions:

- U24Y101: 76 H x 185 W x 75 mm D
(3.0 x 7.28 x 2.94")
- U48Y40: 114 H x 130 W x 87 mm D
(4.49 x 5.12 x 3.44")

REGULATED PSR SERIES

Input: 115V or 230 Vac models

PSR-24S Dimensions:
56 L x 49 W x 81 mm H
(2.2 x 1.9 x 3.2")



- ✓ Regulated and Unregulated Power Supplies for Transducers and Transmitters
- ✓ 48V Available for High-Resistance Loops
- ✓ Compact, Rugged Design

To Order

| MODEL NO. | DESCRIPTION |
|-------------|--|
| PSR-24S | Regulated power supply, 24 Vdc, 400 mA, screw terminal, 115 Vac |
| PSR-24L | Regulated power supply, 24 Vdc, 400 mA, UL, 1.8 m (6') cord with stripped leads |
| PSR-24L-230 | Regulated power supply, 24 Vdc, 400 mA, stripped leads, 230 Vac input, CE |
| U24Y101 | Unregulated power supply, 24 Vdc, 1000 mA, 110 Vac power |
| U24Y101-220 | Unregulated power supply, 24 Vdc, 1000 mA, 220 Vac power |
| U48Y40 | Unregulated power supply, 48 Vdc, 400 mA for long loops (high resistance), 110 Vac |

Comes complete with operator's manual.

Ordering Example: PSR-24L-230, 24 Vdc, 400 mA, stripped leads, 230 Vac input, CE.